


# wave box mit mechanischen Wechselschaltern SPDT


wave box with mechanical switches N.O. / N.C. SPDT



## Varianten Versions




Cherry, D44X



Cherry, D41X

## Technische Daten Technical features

Endschalterfabrikat Producer switch	CHERRY	CHERRY	
Endschaltertyp Switch type	D44X	D41X	
Spannung Voltage	250V	250V	
Maximaler Strom Maximum current	10A (250V AC) / 2,5A (24V DC)	0,1A (250V AC) / 0,1A (24V DC)	
Kontakte Contacts	Silber Silver	Gold Gold	
Temperatur Temperature	(-40°C) -25°C ... +80°C	(-40°C) -25°C ... +80°C	
Bestellnummer Ordering code	EPP2M01, EPE2M01 EAP2M01, EAE2M01	EPP2M01-G, EPE2M01-G EAP2M01-G, EAE2M01-G	



Optionale Ausführungen auf Seite 36  
Optional executions on page 36

Gehäuseinformationen auf Seiten 2-9  
Housing information on pages 2-9

## Artikelnummer Code number

<b>Gehäuse Housing</b> P Polyamid Polyamide A Aluminium Aluminum V Vestamid Vestamide	<b>Brücke Bracket</b> P Polyamid Polyamide E Edelstahl Stainless steel	<b>Schalter Switches</b> 1 Stück Piece 2 Stück Pieces 3 Stück Pieces 4 Stück Pieces	<b>Schalterart Switch type</b> M Mechanisch Mechanical I Induktiv Inductive S Schlitz Slot type D Doppelsensor Double sensor	<b>Bohrbild Hole spacing</b> 00 50x25x20 04 130x30x50 08 130x30x40 01 80x30x20 05 80x30x40 09 50x25x30 02 80x30x30 06 80x30x50 10 F05 03 130x30x30 07 130x30x20	<b>Typ Type</b> Cherry, D44X G Cherry, D41X	<b>Optionale Ausführung Optional execution</b>
--	--	---	--	---	---	--